



DIGISOL®

SWITCHING SOLUTIONS

DIGISOL High Performance SFP Transceivers

DG-SA1030



Key Features:-

- SFP Multisource Agreement (MSA) compliant
- Hot Pluggable
- Low power dissipation
- Single power supply 3.3V

Introduction:-

DIGISOL DG-SA1030 Small form Factor Pluggable (SFP) transceiver modules are specifically designed for the high performance integrated data link over optical fiber. With the hot pluggability, these modules offer an easy way to be installed into SFP ports at any time without the interruption of the host equipments operating online.

Technical Specifications:-

- Connector type: LC Type
- IEEE Standard: IEEE 802.3z
- Wavelength (nm): 850nm
- Fiber type: Multi Mode
- Max Cable Distance: 280-550m

- Case Operating Temperature: 0° ~ 70°
- Storage Relative Humidity: 5% to 95%

Warranty

- DIGICARE One year Warranty



Ordering Information:-

DG-SA1030 : DIGISOL 1000Base-SX SFP Transceiver LC Type (550m)

*Warranty shall be subject to terms and conditions specified in the DIGISOL PRODUCT WARRANTY displayed on the website of the company.

DIGISOL Logos are trademarks and/or registered trademarks of DIGISOL SYSTEMS LIMITED. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here. © 2023 DIGISOL SYSTEMS LIMITED. All rights reserved.

DIGISOL is a Subsidiary of Smartlink Holdings Limited

DIGISOL SYSTEMS LIMITED
CITIPOINT, 7th Floor,
Unit No. B-701, B-702 & B-703,
Andheri-Kurla Road, J. B. Nagar,
Andheri (East),
Mumbai - 400059, INDIA

- 1800-209-3444
- www.digisol.com
- helpdesk@digisol.com

@DIGISOLINDIA

Datasheet Updated: 24th April 2023