



DIGISOL™

SWITCHING SOLUTIONS

DIGISOL 8 Port Gigabit Ethernet Smart Managed Switch with 4 Combo Ports

DG-GS4112

Key Features:-

- Supports up to 8 10/100/1000Mbps Gigabit Ethernet ports and 4 SFP slots
- IEEE 802.1Q VLAN allows network segmentation to enhance performance and security
- Supports Access Control List (ACL)
- Switch capacity: DG-GS4112: 24Gbps, Forwarding rate: 41.6Mpps
- Supports IGMP Snooping v2 / v3
- 8K MAC address table and 10K jumbo frames
- 19-inch rack-mountable metal case



Introduction:-

DIGISOL DG-GS4112 is a Web Managed switching product. It is an intelligent network manageable switch designed for network environments that require high performance, high port density and easy for installation. It provides 8 Gigabit Ethernet and 4 SFP Giga combo ports. It supports VLAN, Port Mirroring and Port Trunking.

Performance and Scalability

It's a great L2 managed switch with 24 Gbps switching capacity. Wire-speed switching performance helps to take full advantage of existing high performance on PCs and laptops by significantly improving the responsiveness of applications and file transfer times. The device also has Four Gigabit SFP ports for high speed uplinks to servers or backbones.

Continuous Availability

IEEE 802.1w Rapid Spanning Tree Protocol provides a loopfree network and redundant links to the core network with rapid convergence, to ensure faster recovery from failed links, enhancing overall network stability and reliability. IEEE802.3ad Link Aggregation Control Protocol (LACP) increases bandwidth by automatically aggregating several physical links together as a logical trunk and providing load balancing and fault tolerance for uplink connections.

Comprehensive QoS

Traffic is prioritized according to 802.1p giving optimal performance to real time applications such as voice and video.

Enhanced Security

Port Security ensures access to switch ports based on MAC address. Thus limiting the total number of devices from using a switch port and protects against MAC flooding attacks.

Simplified Management

User friendly web interface facilitates ease of management. It also supports to be managed and controlled by network station.



DIGISOL™

SWITCHING SOLUTIONS

Technical Specifications:-

Physical Port

- 8 10/100/1000 Base-T Ethernet PoE Ports
- 4 Gigabit Combo (RJ-45/SFP) Ports
- Reset Button: reset to default setting, re-start system
- Console Port: RJ-45

Performance

- Switching Capability: 24Gbps
- MAC Address Table: 8K
- Packet buffer size: 4.1MB
- Jumbo Frame: 10K

L2 Features

- Auto-negotiation for port speed and duplex mode
- Spanning Tree Protocol
 - Support STP / RSTP / MSTP (max 16 instance)
 - Loopback Detection
 - BPDU Filter
 - BPDU Guard
- LLDP, LLDP-MED
- IGMP v1/v2 Snooping: IGMP Querier, Immediate Leave
- MLD Snooping
- MVR
- Multicast: Router Port, Forward Port, Throttling, Filtering
- VLANs
 - 256 IEEE 802.1q tag based VLAN with 4K VLAN ID
 - MAC Based VLAN, Voice VLAN, Guest VLAN, Protocol VLAN, Surveillance VLAN, Management VLAN, GVRP

- Link Aggregation
 - LACP: 8 Groups, 8 Ports/Group
 - Static Trunk

QoS Features

- Queueing Mechanism: SP and WRR
- Classifications based on
 - COS, COS DSCP, IP Precedence
- Each port supports 8 queues
- Rate Limit (Port Based):
 - Ingress/ Egress Port, Egress Queue
- Flow Control

Security

- MAC address Binding
- Support Broadcast storm control
- IP and MAC ACL (IPv4/IPv6)
- RADIUS, TACACS+, AAA
- Port Security, Protected Port
- DOS, Dynamic ARP Inspection
- Management ACL
- DHCP Snooping, DHCP Snooping option 82, IP Source Guard, IP-MAC-Port-VLAN Binding
- 802.1x /Web/MAC based Authentication

Management

- Port Mirroring
- Support traffic statistics
- Provide IPv4 Web-based management
- IPv4 DHCP Client
- Configuration Backup and Recovery
- Dual firmware images and Configuration files
- Error Disabled, Bandwidth Utilization
- SNMP v1/v2c/v3

- Remote Server
- Console, Telnet, SSH, HTTP, HTTPS
- RMON, SNMP
- Ping, Traceroute
- UDLD, EEE
- Copper Test, DDM
- Logging Info, Port Statistics

Power Supply

- AC Power: 100 to 240 V, 50-60 Hz
- Input Surge Protector

Standards

- IEEE 802.3 10BASE-T
- IEEE 802.3u 100BASE-TX
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3az IEEE

Environmental Specifications

- Temperature :
 - Operating: 0°C ~ 40°C
 - Storage: -40°C ~ 70°C
- Humidity:
 - Operating: 10% ~ 90% RH (Non-condensing)
 - Storage: 5% ~ 90% RH (Non-condensing)

Mechanical

- Dimensions (WxDxH): 265mm x 183mm x 44mm
- LED Indicators: Power, Link/Act
- Hardware Factory Reset button

Warranty

- DIGICARE Lifetime Warranty



Ordering Information:-

DG-GS4112: DIGISOL 8 Port Gigabit Ethernet Smart Managed Switch with 4 Combo Ports

*Lifetime Warranty shall be subject to terms and conditions specified in the DIGISOL PRODUCT WARRANTY displayed on the website of the company.

DIGISOL Logos are trademarks and/or registered trademarks of DIGISOL SYSTEMS LIMITED. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here. © 2018 DIGISOL SYSTEMS LIMITED. All rights reserved.



Power Connector

DIGISOL is a Subsidiary of Smartlink Holdings Limited

DIGISOL SYSTEMS LIMITED
215 Atrium Bldg., 2nd Floor,
B-Wing, Opp. Big Cinema,
Courtyard Marriott Compound,
Andheri-Kurla Road,
Andheri (E), Mumbai - 400093.

- 1800-209-3444
- www.digisol.com
- helpdesk@digisol.com

@DIGISOLINDIA