

Technical Specifications

Ethernet

- Operating mode: Store and forward, L2 wire-speed/non-blocking switching engine
- MAC addresses: 8K
- Jumbo frames: 9K Bytes*

Copper RJ45 Ports

- Speed: 10/100/1000 Mbps
- MDI/MDIX Auto-crossover: Support straight or cross wired cables
- Auto-negotiating: 10/100/1000 Mbps speed auto-negotiation; Full and half duplex

SFP (Pluggable) Ports

- Port types supported:
 - SFP (pluggable) Ports 100/1000BaseSFP slot
 - Support 100/1000BaseT SFP transceiver

Network Redundancy

- Fast failover protection rings:
 - Link loss recovery < 20ms
 - Support Single & Multiple rings; Ring coupling; Dual-homing; Chain
- Spanning Tree Protocol: IEEE 802.1D STP, IEEE 802.1w RSTP, IEEE 802.1s MSTP
- Port Trunk with LACP: Static trunk or Dynamic via LACP (Link Aggregation Control Protocol)

Bridge, VLANs & Protocols

- Flow control: IEEE 802.3x (Full Duplex) and Back-Pressure(Half Duplex)
- Max VLANs: 1024
- VLAN Types:
 - Port-based VLANs; MAC-based VLANs; IP Subnet-based VLANs Protocol-based VLANs.
 - IEEE 802.1Q tag-based VLANs
 - IEEE 802.1ad Double Tagging (Q in Q)
- Multicast protocols:
 - IGMP v1, v2 with up to 255 multicast groups
 - IGMP snooping and querying, IGMP snooping v3
 - IPv6 over Ethernet
 - Support of IPv6 Multicast with MLDv1 and MLDv2
- LLDP: IEEE 802.1ab Link layer Discovery Protocol (LLDP)

Traffic management & QoS

- Priority: IEEE 802.1p QoS
- Number of queues per port: 8
- Scheduling schemes: SPQ, WRR
- Traffic Shaper: port-based shaping

Security

- Port security:
 - IP and MAC-based access control
 - IEEE 802.1X authentication Network Access Control
 - RADIUS and TACACS+ AAA (Authentication, Accounting and Authorization)
- Storm Control: Multicast/Broadcast/Flooding

Management

- User Management interfaces:
 - CLI (command line interface), Console
 - WEB-based Management
 - SNMP v1, v2c, v3
 - Telnet

L2-Managed Din-Rail Industrial Ethernet Switch

DG-IS4508HP / DG-IS4512HP / DG-IS4514HP



Product Features & Compliances:

- Provide 4 or 8 10/100/1000 Base TX PoE ports plus 2 or 4 100/1000BaseF SFP slots
- IEEE 802.3af 15.4W / IEEE 802.3at ,30W High Power PoE / IEEE 802.3bt, 60W Ultra PoE (port 1&2 of DG-IS4514HP only)
- Total PoE power budget: 120W (DG-IS4508HP) / 240W (DG-IS4512HP & DG-IS4514HP)
- 9K Jumbo frames
- L2 wire-speed switching engine
- 8K MAC forwarding addresses
- Network redundant LACP, Spanning tree STP, RSTP & MSTP, and quick Ring fail-over protection (< 20 ms)
- Port-based /tag-based VLAN, IEEE 802.1ad/QinQ VLAN, Add/remove VLAN tags,
- Multicasting support IGMP v1/v2, proxy & snooping
- Multicast/Broadcast/Flooding Storm Control
- IEEE802.1x access control
- CLI/Web/SNMP management interfaces
- Dual power input & Reverse power protection

Technical Specifications

- Management Security:
 - HTTPs, SSH
 - Radius Client for Management
- Upgrade & Restore: FTP for Configuration Import/Export, FTP for Firmware Upgrade
- Diagnostic: Syslog
- MIBs:
 - RFC 1757 RMON 1,2,3,9; RFC 2674 Q-Bridge MIB
 - RFC-1213 MIB-II; RFC-1493 Bridge MIB; RFC 2233 IF MIB
- DHCP: Client, Server, Relay, Snooping, Option 82
- NTP/SNTP: Yes
- System status: Device info/status; Ethernet port status; PoE status
- PoE management: Scheduling; power control; PoE PD power consumption

Power

- Power Input: Redundant Input Terminals
- Input voltage range: 46-57 VDC
- Total PoE output power budget:
 - 120W (DG-IS4508HP) /
 - 240W (DG-IS4512HP & DG-IS4514HP)
- PoE PSE port output power management: Scheduling; power control; PoE PD power consumption
- Reverse power protection: Yes
- Power consumption: 15W without PD loading

Indicators

- Power Status indication: Indication of power input status
- Ethernet port indication: Link & Speed
- PoE status: Indication of PoE Power applying

Environmental & Compliances

- Operating temperature range:
 - 40 to +75°C (cold startup at -40°C)
- Storage temperature range: -40 to +85 °C
- Humidity (non-condensing): 5 to 95% RH
- RoHS: RoHS (Pb free)
- MTBF: > 25 years

Mechanical

- Ingress protection: IP30
- Installation option: DIN-Rail mounting, Wall mounting
- Dimension: 77mm(W) x 154mm(H) x 128mm(D)
- Weight: 1410 g

Ordering Information:

DG-IS4508HP: DIGISOL industrial 8-port managed PoE switch with 4 Giga PoE ports & 2 Giga ports & 2 SFP ports

DG-IS4512HP: DIGISOL industrial 12-port managed PoE switch with 8 Giga PoE ports & 4 SFP ports

DG-IS4514HP: DIGISOL industrial 14-port managed PoE switch with 8 Giga PoE ports (Ports 1 & 2 supports Ultra PoE 60W) & 2 Giga ports & 4 SFP ports

** Please refer warranty document on www.digisol.com

DIGISOL Logos are trademarks and/or registered trademarks of DIGISOL SYSTEMS LIMITED. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here. © 2017 DIGISOL SYSTEMS LIMITED. All rights reserved.

Updated: 08/03/2017

DIGISOL is a Subsidiary of Smartlink Network Systems Ltd.