



DIGISOL™

FIBER

STRUCTURED CABLING SYSTEMS

DIGISOL Fiber LIU, Wall Mount Type

Introduction:-

DIGISOL 12 Port Configurable Fiber LIU is a wall mount unit for storing and terminating incoming Fiber Cable. Management rings within system accommodates excess fiber cordage behind the adapter panel and maintain fiber bend radius. Wall mount type LIU comes with a keyed lock, to provide a compact, secure termination.

Key Features:-

- Cold Rolled Steel as Raw Material
- Consist of Top Cover and Bottom Panel
- Easy to Assemble and Dissemble
- Three Types of Input Holes
- Cable Entry Through Water Proof Cable Clamp
- SC or LC Adapter Interface
- Patch Cord with Bend Radius Guides Minimize Macro Bending
- Comprehensive Accessory Kits for Cable Entry and Fiber Management



Technical Specifications:-

Adapter Capacity	: Max. 24
Adapter Plates	: 2
Splice Tray	: 1

Mechanical Specifications:-

Dimensions (mm)	: 320 X 250 X 80
Body Material	: SPCC Black Powder Coating

Ordering Information:-

Product Code	Description
DGF-LXXXUXX-2W	DIGISOL Fiber LIU, Wallmount Type, Unloaded, 24 Port

Adapter Panels for the Wall Mount LIU:

DGF-APDSC1-12	1 X 12 Adapter Panel - SC Duplex
DGF-APDSC1-3	1 X 3 Adapter Panel - SC Duplex
DGF-APDSC1-6	1 X 6 Adapter Panel - SC Duplex
DGF-APSFC1-12	1 X 12 Adapter Panel - FC Simplex
DGF-APSLC1-12	1 X 12 Adapter Panel - LC Simplex
DGF-APSLC1-24	1 X 24 Adapter Panel - LC Simplex
DGF-APSLC1-6	1 X 6 Adapter Panel - LC Simplex
DGF-APSMT1-12	1 X 12 Adapter Panel - MTRJ Simplex
DGF-APSSC1-12	1 X 12 Adapter Panel - SC Simplex
DGF-APSSC1-6	1 X 6 Adapter Panel - SC Simplex
DGF-APSST1-12	1 X 12 Adapter Panel - ST Simplex
DGF-APXXXX-X	1 X 12 Adapter Panel - Blank