



DIGISOL®

SWITCHING SOLUTIONS

DIGISOL L2 Managed Din-Rail Industrial Gigabit Switch

DG-IS4512E



Key Features:-

- 8 x 10/100/1000M RJ-45 ports + 4 x 1000M SFP
- 8K MAC forwarding address
- Support fast ring, Support 30 No of switches max. in a cascade systems, Self-healing in 20ms Min.
- Support relay alarm output for power off, link failure
- IP30 Enclosure
- 12~57VDC Dual power input and relay output
- -40 ~ 75°C wide-range operating temperature
- 6KVA Lightning & Surge Protection



Introduction:-

DIGISOL DG-IS4512E switch is designed for Industrial applications. Thanks to its wide operating temperature it can operate reliably in extremely harsh environments. Designed with 8 10/100/1000M ports & 4 1000M SFP ports which provides abundant and flexible connection. The switch support surge protection to ensure system stability for greater user flexibility.

Technical Specifications:-

Communications

- Standard : IEEE 802.3, 802.3u, 802.3x, 802.3z, 802.3ab
- LAN : 10/100/1000Base-T (X), 1000Base-SX/LX,
- Transmission Distance:
Up to 100 m (4 - wire Cat.5e, Cat.6
RJ45 cable suggested for Gigabit port)
SFP: Up to 80 km (depends on SFP)
- Transmission Speed:
Ethernet: 10/100/1000 Mbps
Fiber: 1000 Mbps

Interface

- Connectors :
8 x RJ45 (Gigabit), 4 x SFP Ports
1 removable 6-contact terminal block
(Phoenix terminal)
- LED Indicators :
RJ-45: Link/Activity, SFP: Link/Activity

Mechanism

- Enclosure : IP30, Metal shell with solid mounting kits
- Dimensions : 159 x 110 x 46.5 mm
- Mounting : Din-rail & Wall mounting

Power

- Power Input : 12VDC, Redundant
Dual Power Input.

Environment

- Operating Temperature : -40 ~ 75°C
- Storage Temperature : -40 ~ 85°C
- Operating Humidity : 05 ~ 95%
(non condensing)
- Storage Humidity : 10 ~ 95%
(non-condensing)

Ordering Information:-

DG-IS4512E**: DIGISOL Industrial L2 Managed switch with 8 Gigabit ports & 4 Gigabit SFP ports

*Limited Lifetime Warranty shall be subject to terms and conditions specified in the DIGISOL PRODUCT WARRANTY displayed on the website of the company.

**Power Supply is not included in standard package

DIGISOL Logos are trademarks and/or registered trademarks of DIGISOL SYSTEMS LIMITED. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here. © 2020 DIGISOL SYSTEMS LIMITED. All rights reserved.

DIGISOL is a Subsidiary of Smartlink Holdings Limited

DIGISOL SYSTEMS LIMITED
215 Atrium Bldg., 2nd Floor,
B-Wing, Opp. Big Cinema,
Courtyard Marriott Compound,
Andheri-Kurla Road,
Andheri (E), Mumbai - 400093.



1800-209-3444



www.digisol.com



helpdesk@digisol.com

@DIGISOLINDIA

Datasheet Updated: 06th May 2020