



DIGISOL™

SWITCHING SOLUTIONS

DIGISOL L2-Managed Din-Rail Industrial Gigabit PoE Switch

DG-IS4506HPE

Key Features:-

- 4 x 10/100/1000M RJ-45 ports + 2 x 1000M SFP
- 8K MAC forwarding address
- Support fast ring, Self-healing in 20ms Min.
- Support relay alarm output for power off, link failure
- Provides 4 PoE ports, with 60W PoE budget
- IP30 Enclosure
- 48~57VDC Dual power input and relay output
- -40 ~ 75°C wide-range operating temperature
- 6KVA Lightning & Surge Protection



Introduction:-

DIGISOL DG-IS4506HPE switch is designed for Industrial applications. Thanks to its wide operating temperature it can operate reliably in extremely harsh environments. Designed with 4 10/100/1000M PoE ports & 2 1000M SFP ports which provides abundant and flexible connection. The switch support surge protection to ensure system stability for greater user flexibility.

Technical Specifications:-

Communications

- Standard : IEEE 802.3, 802.3u, 802.3x, 802.3z, 802.3ab, 802.3af, 802.3at
- LAN : 10/100/1000Base-T (X), 1000Base-SX/LX,
- Transmission Distance:
Up to 100 m (4 - wire Cat.5e, Cat.6
RJ45 cable suggested for Gigabit port)
SFP: Up to 80 km (depends on SFP)
- Transmission Speed:
Ethernet: 10/100/1000 Mbps
Fiber: 1000 Mbps

Interface

- Connectors :
4 x RJ45 (Gigabit), 2 x SFP Ports
1 removable 6-contact terminal
block(Phoenix terminal)
- LED Indicators : RJ-45: Link/Activity
- PoE Budget : 60W
SFP: Link/Activity

Mechanism

- Enclosure : IP30, Metal shell with
solid mounting kits
- Dimensions : 159 x 110 x 46.5 mm
- Mounting : Din-rail & Wall mounting

Power

- Power Input : 48~57V DC, Redundant
Dual Power Input.

Environment

- Operating Temperature : -40 ~ 75°C
- Storage Temperature : -40 ~ 85°C
- Operating Humidity : 05 ~ 95%
(non condensing)
- Storage Humidity : 10 ~ 95%
(non-condensing)



DIGISOL™

SWITCHING SOLUTIONS

DIGISOL L2-Managed Din-Rail Industrial Gigabit PoE Switch

Software Parameter:-

Port Management

- Support Port Enable/Disable
- Support Port Rate Settings
- Support Port Full-duplex Mode
- Support IEEE802.3x Flow Control
- Support Port Name Change

VLAN

- Support 4K VLAN
- Support 802.1Q Protocol-Based VLAN
- Support Port-Based VLAN

QoS

- Support QoS
- Support 8-Level Priority management for switching
- Support WRR
- Support 820.1P and DSCP Priority

Multicast Management

- Support SNMP V1/V2/V3 Protocol
- Support IGMP Snooping

POE Management

- Support Total Power Consumption Control
- Support PoE ON/OFF
- Support Single Port 60W max. Power Change and Port Output Priority

Alarm signal output by relay

- Support relay alarm for power off, ports network link-off, ports PoE off

Safety Character

- Support IP, MAC, Port, VLAN Combination and Binding
- Support MAC address auto-learning, aging & filter
- Support Port Isolation, Port Speed-Limited
- Support RSTP
- Support Fast-Ring
- Support 5 groups of 8-Port trunk
- Support RADIUS Authentication & 802.1X Authentication

System Management& Maintenance

- Support WEB Management, CLR Settings and telnet Settings
- Support CLR Settings
- Support FTP/TFTP/HTTP Web Upgrading
- Support Flow Calculate
- Support MAC address Form Search
- Support IP Address, DNS Server Change
- Support Username & Password Change
- Support History Record, Journal management
- Support System settings Backup

Ordering Information:-

DG-IS4506HPE**: DIGISOL Industrial L2 Managed switch with 4 Gigabit PoE ports & 2 Gigabit SFP ports

*Limited Lifetime Warranty shall be subject to terms and conditions specified in the DIGISOL PRODUCT WARRANTY displayed on the website of the company.

DIGISOL Logos are trademarks and/or registered trademarks of DIGISOL SYSTEMS LIMITED. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here. © 2019 DIGISOL SYSTEMS LIMITED. All rights reserved.

DIGISOL is a Subsidiary of Smartlink Holdings Limited

DIGISOL SYSTEMS LIMITED
215 Atrium Bldg., 2nd Floor,
B-Wing, Opp. Big Cinema,
Courtyard Marriott Compound,
Andheri-Kurla Road,
Andheri (E), Mumbai - 400093.



1800-209-3444



www.digisol.com



helpdesk@digisol.com

[@DIGISOLINDIA](https://www.facebook.com/DIGISOLINDIA)