



DIGISOL XPON ONU 300Mbps
Wireless Router with 1 PON, 1 GE +
1 FE LAN Port & 1 FXS Port

DG-GR1321

Key Features:-

- Plug and play, features auto-detecting, auto-configuration and auto firmware upgrade, etc.
- Integrated OAM/OMCI remote configuration and maintenance function
- Support IGMP Snooping
- Support 802.11n WiFi (2T2R) function
- · Support NAT, Firewall function
- · Support IPv4 and IPv6 dual stack
- Integrated line testing compliant with GR-909 on POTS



Introduction:-

DIGISOL DG-GR1321 terminal devices are designed for fulfilling FTTH and triple play service demand of fixed network operators or cable operators. These boxes are based on the mature Gigabit EPON/GPON technology, which have high ratio of performance to price, and the technology of 802.11n WiFi (2T2R), Layer 2/3 and high quality VoIP as well. They are highly reliable and easy to maintain, with guaranteed QoS for different service. And they are fully compliant with technical regulations such as IEEE802.3ah. It works on both GEPON/GPON technology.

Technical Specifications:-

HARDWARE PARAMETER: PON Interface

 SC single-mode/ single-fiber, Upstream 1.25Gbps, Downstream 2.5Gbps

Wavelength

Tx 1310nm, Rx 1490nm

Rx Sensitivity

• -8dBm to -27dBm

Optical Type

• SC/PC

Interface Type

1*10/100/1000Mbps +
 1*10/100Mbps +

- Auto adaptive Ethernet interfaces, Full/Half Duplex, RJ45 Connector
- 1 FXS Port

Wireless

- Compliant with IEEE802.11b/g/n, 300Mbps, 2T2R with Two external antenna
- Support WEP and WPA/WPA2 security protocols.

Indicators

• 8, For PWR, PON, LOS, LAN2, LAN1, TEL, PAIR, Wi-Fi

SOFTWARE PARAMETER:

VLAN

- Support VLAN,
- 1:1 VLAN,
- VLAN reusing,
- VLAN trunk

Multicast

 Support IPv4 IGMP Snooping and IPv6 MLD Snooping

QoS

• Integrated IEEE802.1p QoS with four level priority queues





DIGISOL XPON ONU 300Mbps Wireless Router with 1 PON, 1 GE + 1 FE LAN Port & 1 FXS Port

Technical Specifications:-

- Support IPv4, IPv6 and IPv4/ Ipv6 dual stack
- Support DHCP/ PPPOE/ Static
- Support Static route
- Support NAT
- Support Virtual Server

DHCP

Support DHCP server

VolP

- Support SIP protocol
- Support Voice coding: ITU-T G.711/ G.723/G.726/G.729
- Support Echo cancellation exceeding ITU-T G.165/G.168-2002, up to 128ms tail length

- Support high/low speed fax/Modem, bypass fax, and T38 fax
- Support InBand / RFC2833/SIP INFO, Md5 authentication, call forward, call waiting, hot-line call, and all kinds of value-added voice service. Multi-party conferencing
- Support Line testing according to GR-909

Wireless

- · Support 802.11b/g/n and Mixed mode
- Support 4 SSID
- Support No-auth, WEP, WPA-PSK and WPA2-PSK function with AES, TKIP encryption

Management

- Support WEB
- Support Telnet
- Support Tr069

Operating Temperature

• -5~+55°C

Operating Humidity

10~90% (non-condensed)

Store Temperature

• -30~+60°C

Store Humidity


• 10 ~ 90% (non-condensed)

Ordering Information:-

DG-GR1321: DIGISOL XPON ONU 300Mbps Wireless Router with 1 PON, 1 GE + 1 FE LAN Port & 1 FXS Port

*Warranty shall be subject to terms and conditions specified in the DIGISOL PRODUCT WARRANTY displayed on the website of the company.

DIGISOL Logos are trademarks and/or registered trademarks of DIGISOL SYSTEMS LIMITED. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here. © 2022 DIGISOL SYSTEMS LIMITED. All rights reserved.





DIGISOL SYSTEMS LIMITED

215 Atrium Bldg., 305, A-Wing, 3rd Floor, Opp. Big Cinema, Courtyard Marriott Compound, Andheri-Kurla Road, Andheri (E), Mumbai - 400093.







1800-209-3444 🌘 www.digisol.com 🔯 helpdesk@digisol.com

¶@DIGISOLINDIA