



DIGISOL®

SWITCHING SOLUTIONS

DIGISOL 48 Port L2+ 10G Access PoE Switch

DG-GS4652HP-XS



Key Features:-

- 10G Uplink Access Switch
- 48 x 10/100/1000Base-T PoE + 4x 10GE (SFP+)
- Forwarding type: Store and forward
- Energy Efficient with Energy saving feature
- PoE+ upto 740W
- Advanced Security features including RADIUS & TACACS+ Authentication
- Supports Ethernet Ring Protection Switching (ERPS)
- Supports MVR (Multicast VLAN Register)
- VSF (Virtual Switch Framework)



Introduction:-

DIGISOL DG-GS4652HP-XS switch is a Layer 2 Gigabit intelligent switch. It supports comprehensive QoS, enhanced VLAN functions (VLAN, Voice VLAN, QinQ, N: 1 VLAN Translation etc.), Ethernet Ring Protection Protocol (G.8032), classified bandwidth control, intelligent security control, OAM (Operations, Administration and Maintenance), manageability functions and services DG-GS4652HP-XS switch also offers green features like auto speed Fan design feature, which can dramatically lower power consumption. This switch is equipped with GE PoE ports and 4 SFP+ uplink ports, it integrates advanced management and security functions to provide performance and scalability.

Key Features and Benefits:-

- **10G Uplink Access Switch**
Equipped with the full GE ports and 4 SFP+ uplink ports, DG-GS4652HP-XS provides a solid foundation and more than enough bandwidth for your business applications today and in the future.
- **L3 Forwarding**
DG-GS4652HP-XS supports L3 forwarding allowing you to segment your network into workgroups and communicate across VLANs without degrading application performance.
- **Enhanced Security**
IEEE 802.1X port-based access control ensures all users are authorized before being granted access to the network. User authentication is carried out using any standard-based RADIUS server. Access Control Lists (ACLs) can be used to restrict access to sensitive network resources by denying packets and forward by different policies. User-defined ACL provides more flexible access control for users. DG-GS4652HP-XS supports DHCP snooping, which prevents DHCP attacks from an illegal DHCP Server by setting trust ports and untrust ports. With DHCP Snooping binding and option82 enabled, it can combine modules like dot1x and ARP or implement user-access-control independently.
DG-GS4652HP-XS supports abundant L2 security features such as ARP guard, Anti-ARP scanning and other ARP technology to protect network security and reliability.
- **High Reliability**
DG-GS4652HP-XS supports 4 10G uplink ports, which could be designed to offer redundant uplinks with various ring protection applications, effectively raised the expansibility and performance of the network. G.8032 provides sub-50ms protection and recovery switching for Ethernet traffic in a ring topology. DG-GS4652HP-XS supports G.8032 v2 and can be deployed in a variety of complex network topologies including single ring, tangent ring, intersecting rings, double rings, and other home networking.
- **Abundant Multicast Features**
DG-GS4652HP-XS also supports MVR (Multicast VLAN Register), selectively allows traffic to cross between different VLANs for bandwidth and security reasons. With the MVR Trunk function, which could associate multicast VLAN to trunk port, DG-GS4652HP-XS combines the VLAN data into the same link, saving lots of resources for users. DG-GS4652HP-XS could prevent multicast traffic from flooding via IGMP Snooping, while multicast traffic is only forwarded to ports associated with multicast devices.



DIGISOL®

SWITCHING SOLUTIONS

Technical Specifications:-

HARDWARE FEATURES

Ports :

- 48 x 10/100/1000Base-T PoE+
4 x 10GE (SFP+), Auto-MDIX

Management port :

- 1x MGMT port
- 1x Console port
- 1x USB2.0 interface

Performance :

- Switching Capacity : 176Gbps
- Forwarding Rate : 131Mpps
- MAC address : 16K
- Jumbo Frame : 10K
- Packet buffer: 24Mbits
- ACL Table : 512
- Queues Per Port : 8
- VLAN Table : 4K

Physical :

- Dimension (W×H×D) :
440mm x 44mm x 320mm
- Working Temperature : 0°C~50°C
- Storage Temperature : -40°C~70°C
- Relative Humidity : 5%~95%,
non-condensing

MAIN FEATURES

VLAN :

- Port-based VLAN
- IEEE802.1Q
- Private VLAN, Protocol VLAN,
Voice VLAN, MAC VLAN
- Q-in-Q, Selective QinQ,
Flexible QinQ
- VLAN Translation, N:1 VLAN
Translation

L3 Features :

- Static Routing, PBR

DHCP :

- IPv4/ IPv6 DHCP Client
- IPv4/ IPv6 DHCP Relay Option 82,

- Option 37/38
- IPv4/ IPv6 DHCP Snooping
- IPv4/ IPv6 DHCP Server

Reliability :

SPANNING TREE PROTOCOL

- 802.1D Spanning Tree
- 802.1w Rapid Spanning Tree
- 802.1s Multiple Spanning Tree
- Root Guard
- BPDU Guard
- BPDU Forwarding
- TCN filtering

LACP :

- 64 groups / 8 ports

L2 Ring Protection

- MRPP
- ERPS (G.8032)
- Loopback Detection
- Fast Link

Security Features :

- IP ACL, MAC ACL, MAC-IP ACL,
User-Defined ACL
- Time Range ACL
- ACL rule can be configured on port,
VLAN interface
- Storm Control based on packets
- Port Security, MAC Limit based
on VLAN and Port
- Anti-ARP-Spoofing, Anti-ARP-Scan,
ARP Binding
- ND Snooping
- Dynamic ARP Inspection (DAI)
- IEEE 802.1x
- Authentication, Authorization,
Accounting
- Radius & TACACS+

Multicast :

- IGMP Snooping (V1,v2,v3)
- IGMP Proxy, IGMP v3
- MLD v1/ v2 Snooping

Qos Features :

- 8 Queue Per Port
- Bandwidth Control
- Flow Redirect
- Classification based on ACL
(Access Control List), VLAN ID,
COS, TOS, DSCP)
- Policy Based on Port & VLAN,
- Single rate single barrel double color
for policing
- SP+ SDWRR, DWRR, SP DWRR for
Scheduling
- Match the IP fragmentation of
message

Maintenance and Operation

Management :

- TFTP/FTP
- CLI, Telnet, Console
- Web/SSL (IPv4/IPv6)
- SSH (IPv4/IPv6)
- SNMPv1/v2c/v3, SNMP Trap
- Public & Private MIB interface
- RMON 1,2,3,9
- Ping, Trace Route
- Radius Authentication
- Syslog (IPv4/IPv6)
- SNT/NT (IPv4/IPv6)
- Dual IMG, Multiple Configuration
Files
- Port Mirror, RSPAN, sFlow
- VCT, DDM, OAM
- ULDP (Like Cisco UDLD)
- LLDP/LLDP MED

Power :

- Power Input : 100~240VAC, 50~60Hz
- Power Consumption : <897W
- PoE: IEEE 802.3af PoE (15.4W)
IEEE 802.3at PoE+ (30W)
- PoE output: 740W

Green Energy :

- Auto-Speed Fan

Ordering Information:-

DG-GS4652HP-XS: DIGISOL L2+ Full Gigabit Access Switch with 48 *10/100/1000Base-T PoE and 4 *10GE(SFP+) ports, static routing, 1 fixed AC power, PoE output: 740W

*Warranty shall be subject to terms and conditions specified in the DIGISOL PRODUCT WARRANTY displayed on the website of the company.

DIGISOL Logos are trademarks and/or registered trademarks of DIGISOL SYSTEMS LIMITED. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here. © 2023 DIGISOL SYSTEMS LIMITED. All rights reserved.

DIGISOL is a Subsidiary of Smartlink Holdings Limited

DIGISOL SYSTEMS LIMITED
CITIPOINT, 7th Floor,
Unit No. B-701, B-702 & B-703,
Andheri-Kurla Road, J. B. Nagar,
Andheri (East),
Mumbai - 400059, INDIA



1800-209-3444



www.digisol.com



helpdesk@digisol.com

Rear View :



f@DIGISOLINDIA