

## DIGISOL 10GE L3 Ethernet Switch

### DG-GS2628HPSE2

#### Key Features:-

- Supports 24 GE TX Ports with 4 10GE SFP+ Ports
- Advanced Hardware Architecture and Industry-leading Port Density
- Layer-3 Routing Functions
- Versatile IPv6 Solution
- Complete Security Mechanism
- Innovative Virtual Cluster Switching Technique
- Industrial Ethernet Ring with Zero Delay and Zero Packet Loss
- Versatile IPv6 Solutions
- Supports multiple queue schedule algorithms
- Supports the IPv6 protocol suite
- Supports perfect security authentication mechanisms
- Supports a perfect ring detection mechanism to ensure the long-term stable running of network



#### Introduction:-

**DIGISOL** DG-GS2628HPSE2 is a next generation aggregation 10GE switch. It is targeted at medium to large networks like government and enterprise networks, Internet cafe and disk-less working environment. It is developed on the basis of high-performance hardware and a software platform. It supports functions such as powerful ACL, flexible QinQ, 1:1 or N:1 VLAN switching, Ethernet OAM, QoS and industry level 10GE Ether-ring, ensuring this switch meets the application requirements in all kinds of complicated sites. It also supports layer-3 routing protocol.

#### Technical Specifications:-

Specifications	DG-GS2628HPSE2
Interface	24GE TX ports, 4 10GE/GE SFP+ ports
Console	1 RJ45 port
Backplane	128Gbps
Forwarding rate (Mpps with 64 bytes)	96 Mpps
Chassis - Dimensions (WxDxH)(mm)	440x210x44
Chassis - weight (kg) (empty)	3
Package Dimensions (WxDxH)(mm)	555x295x88
Package - weight (kg)	4.1
Power consumption (no load)	< 25W
Power consumption (Full load)	< 408W
Power supply (AC: 100-240V)	410W
PoE Power Budget	370W

Specifications	DG-GS2628HPSE2
Total output BTU (1000BTU/H=293W)	1392.49
Noise@25°C (dBA)	37.5
MTBF(H)	>200,000
Forwarding mode	Store-forward
Flash (MB)	16
DRAM (MB)	256
MAC	16K
Buffer size(MB)	1.5
Jumbo frame	Upto 12K
Interface VLAN	64
Routing entries (IPv4/v6)	502/132
Surge protection	6kv port and 4kv power supply

# DIGISOL<sup>®</sup>

## SWITCHING SOLUTIONS



### Technical Specifications:-

#### VLAN

- 4K Active VLAN
- QinQ & Selective QinQ
- GVRP
- Private VLAN
- Voice-VLAN
- Spanning Tree:
  - 802.1D (STP), 802.1W (RSTP), 802.1Q(PVST+) and 802.1S (MSTP)
- BPDU guard, Root guard and Loopback guard

#### Multicast

- IGMP v1/v2/v3
- IGMP Snooping
- IGMP Fast Leave
- MVR, IGMP filter

#### IP

- Static route, RIP, OSPF,
- IPv4/IPv6 Dual stack

#### IPv6

- ICMPv6, DHCPv6, ACLv6
- IPv6 Telnet
- IPv6 neighbor discovery
- Path MTU discovery
- MLD V1/V2, MLD snooping
- IPv6 Static Routing
- RIPng, OSPFv3
- Manual tunnel
- ISATAP tunnel 6 to 4 tunnel

#### QoS

- CAR, HQoS
- MAC/IP/TCP/UDP/VLAN/COS/DSCP/TOS based QoS
- 802.1P/ DSCP priority re-labeling
- SP, WRR, and SP+WRR
- Tail-Drop
- WRED
- flow monitoring and traffic shaping

#### Security

- Port isolation
- Port security and IP+MAC+port binding
- MAC sticky
- DAI & IP source guard (IPv4)
- IEEE 802.1x, AAA Radius and TACACS+
- L2/L3/L4 ACL flow identification and filtration
- Anti-attack from DDoS
- TCP's SYN Flood, UDP Flood, etc.
- Broadcast/multicast/unknown unicast storm-control
- BMD5, SHA-256, RSA-1024, AES256, etc.

#### DHCP

- DHCP server/relay/client
- DHCP snooping/option82

#### Reliability

- Static/LACP link aggregation, Interface backup
- EAPS and ERPS
- ISSU Uninterrupted system upgrade
- Upto 4 Units per stack
- VRRP
- UDLD

#### Management

- Command-Line-Interface (CLI) through console, Telnet, SSHv1/v2 (similar to Cisco)
- Simple web-based GUI (http, https)
- SNMP v1/v2/v3, RMON
- TFTP, FTP, SFTP
- NTP, ZTP, SPAN, RSPAN

#### Accessories

- Power cord
- Rack mounting kits
- Console cable

#### Environment

- Operating temperature: 0°C -50°C
- Operating humidity: 10%-90% non-condensing
- Storage temperature: -20°C to -70°C
- Storage humidity: 5%-95% non-condensing

### Ordering Information:-

**DG-GS2628HPSE2: DIGISOL Ethernet Layer-3 lite POE switch with 24 GE ports and 4 10GE ports. Standard AC220V power supply, 370W PoE power.**

\*Warranty shall be subject to terms and conditions specified in the DIGISOL PRODUCT WARRANTY displayed on the website of the company.

DIGISOL Logos are trademarks and/or registered trademarks of DIGISOL SYSTEMS LIMITED. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here. © 2025 DIGISOL SYSTEMS LIMITED. All rights reserved.

