

DIGISOL 10GE L3 Lite Ethernet Switch

DG-GS2628FSE2-B2



Key Features:-

- Supports 16 SFP Ports + 8 Combo Ports & 4 10GE SFP+ Ports
- Versatile IPv6 Solution
- Supports VSS stacking
- Standard 19-inch rack-mount
- Supports EAPS & ERPS ring technology



Introduction:-

DIGISOL DG-GS2628FSE2-B2 is a next generation aggregation 10GE switch. It is targeted at medium to large networks like government and enterprise networks, Internet cafe and disk-less working environment. It is developed on the basis of high-performance hardware and a software platform. It supports functions such as powerful ACL, flexible QinQ, 1:1 or N:1 VLAN switching, Ethernet OAM, QoS and industry level 10GE Ether-ring, ensuring this switch meets the application requirements in all kinds of complicated sites. It also supports layer-3 routing protocol.

Technical Specifications:-

Item	DG-GS2628FSE2-B2
Interface	16 SFP Ports + 8 Combo Ports & 4 10G SFP+ ports, Console 1 RJ45 port
Backplane	128Gbps
Forwarding rate (Mpps with 64 bytes)	96Mpps
Flash (MB)	16
DRAM (MB)	256
Jumbo frame	9K
MAC	16K
Buffer size (MB)	1.5
Interface VLAN	64
Routing table	512
Chassis - Dimensions (WxDxH)(mm)	440x280x44
Chassis - weight (kg) (empty)	4
Package Dimensions (WxDxH)(mm)	575x448x94
Package - weight (kg)	5.2
Power consumption (no load)	< 18W
Power consumption (Full load)	< 38W
Power supply	DUAL AC 100-240V
Fan	2
Total output BTU (1000BTU/H=293W)	153.58
Noise@25°C (dBA)	45
MTBF(H)	>200,000

DIGISOL[®]

SWITCHING SOLUTIONS



Technical Specifications:-

MAIN FEATURES:

Item	DG-GS2628FSE2-B2
VLAN	4K Active VLAN
	QinQ & Selective QinQ
	GVRP
	Private VLAN
	Voice-VLAN
Spanning Tree	802.1D (STP), 802.1W (RSTP) and 802.1S (MSTP)
	BPDU guard, root guard and loopback guard
Multicast	IGMP v1/v2/v3, IGMP Snooping, IGMP Fast Leave
	MVR, IGMP filter
IP	Static route
	RIP, OSPF, IPv4 Dual stack
IPv6	ICMPv6, DHCPv6, ACLv6
	IPv6 Telnet
	IPv6 neighbor discovery
	Path MTU discovery
	MLD V1/V2, MLD snooping
	IPv6 Static Routing
	RIPng, OSPFv3
	Manual tunnel
	ISATAP tunnel 6 to 4 tunnel
QoS	CAR, HQoS
	MAC/IP/TCP/UDP/VLAN/COS/DSCP/TOS based QoS
	802.1P/ DSCP priority re-labeling
	SP, WRR, and SP+WRR
	Tail-Drop
	WRED
	flow monitoring and traffic shaping
Security	Port isolation
	Port security and IP+MAC+port binding
	MAC sticky
	DAI & IP source guard (IPv4)
	IEEE 802.1x, AAA Radius and TACACS+
	L2/L3/L4 ACL flow identification and filtration
	Anti-attack from DDoS
	TCP's SYN Flood, UDP Flood, etc.
	Broadcast/multicast/unknown unicast storm-control
	MD5, SHA-256, RSA-1024, AES256, etc.
DHCP	DHCP server/relay/client
	DHCP snooping/option82
Reliability	Static/LACP link aggregation, Interface backup
	EAPS and ERPS
	ISSU Uninterrupted system upgrade

Technical Specifications:-

MAIN FEATURES:

Item	DG-GS2628FSE2-B2
	Upto 4 Units per stack
	VRRP
	UDLD
Management	Console, Telnet, SSH v1/2, HTTP, HTTPS, SNMP v1/v2/v3, RMON
	TFTP, FTP, SFTP
	NTP, ZTP, SPAN, RSPAN
	Dying gasp*
Accessories	Power cord
	Rack mounting kits
	Console cable
Environment	Operating temperature: 0°C -50°C
	Operating humidity: 10%-90% non-condensing
	Storage temperature: -20°C to -70°C
	Storage humidity: 5%-95% non-condensing

Rear View :



Ordering Information:-

DG-GS2628FSE2-B2: DIGISOL Ethernet Layer-3 lite switch with 16-Port Gigabit SFP + 8-Port RJ45/SFP Combo + 4-Port 10G SFP+ (Dual AC-220V power supply, with cooling fan, 1U, standard 19-inch rack-mounted installation)

*Warranty shall be subject to terms and conditions specified in the DIGISOL PRODUCT WARRANTY displayed on the website of the company.

DIGISOL Logos are trademarks and/or registered trademarks of DIGISOL SYSTEMS LIMITED. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here. © 2024 DIGISOL SYSTEMS LIMITED. All rights reserved.

DIGISOL is a Subsidiary of Smartlink Holdings Limited

DIGISOL SYSTEMS LIMITED
CITIPOINT, 7th Floor,
Unit No. B-701, B-702 & B-703,
Andheri-Kurla Road, J. B. Nagar,
Andheri (East),
Mumbai - 400059, INDIA

1800-209-3444
www.digisol.com
helpdesk@digisol.com

@DIGISOLINDIA