

DIGISOL High Performance SFP Transceivers

DG-SA1133I



Key Features:-

- SFP Multisource Agreement (MSA) compliant
- Hot Pluggable
- Supports 1.25Gb/s
- Low power dissipation
- Single power supply 3.3V
- Compatible with Industrial Grade devices



Introduction:-

DIGISOL family of Small form Factor Pluggable (SFP) transceiver modules are specifically designed for the high performance integrated data link over optical fiber. With the hot pluggability, these modules offer an easy way to be installed into SFP ports at any time without the interruption of the host equipments operating online.

Technical Specifications:-

- Connector: LC Type
- IEEE Standard: IEEE 802.3z
- Wavelength (nm): 1310nm
- Fiber Type: Single Mode
- Max Cable Distance: upto 20Km
- Case Operating Temperature: -40° ~75°C
- Storage Relative Humidity: 5% to 95%

Ordering Information:-

DG-SA1133I: DIGISOL 1.25GBase-LX SFP Transceiver LC Type (20kms)

*Warranty shall be subject to terms and conditions specified in the DIGISOL PRODUCT WARRANTY displayed on the website of the company.

DIGISOL Logos are trademarks and/or registered trademarks of DIGISOL SYSTEMS LIMITED. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here. © 2025 DIGISOL SYSTEMS LIMITED. All rights reserved.