DIGISOL®

SWITCHING SOLUTIONS

INDIA'S OWN IT NETWORKING CHOICE

DIGISOL Gigabit PoE Intelligent Switch

DG-GS2620HPE/C

3 YEARS WARRANTY*



Key Features:-

- 16 10/100/1000Mbps BaseT PoE ports
- 2x1G BaseT/SFP Combo ports
- 2x1G SFP ports
- L3 features like RIP, OSPF
- Advanced QoS
- 4KV Thunder protection
- STP, RSTP, MSTP
- ZTP (Zero-Touch-Provisioning)
- L2 multicast functions like IGMP snooping
- ISSU - Service Software Up-grade

Introduction:-

DIGISOL DG-GS2620HPE/C is a fully managed new-generation intelligent PoE access switch designed for medium and large networks. Based on the new-generation high-performance hardware, it supports functions such as ACL, QinQ and QoS. Its simple management mode and flexible installation can meet the requirement of any complicated scenarios. Complete L2+ and additional, L3 lite features makes it an excellent choice for small, medium or enterprise level networks.

Product Characteristics:-

Intelligent PoE+

DG-GS2620HPE/C supports IEEE 802.3af/at PoE standard, and power mapping scales up to a maximum of 250W of PoE+ power.
The PoE+ power to the PD is maintained during a switch reload. It supports both manual and dynamic PoE power allocation. It supports up to 4KV thunder-proof of the PoE port and power supply.

Enhanced QoS

DG-GS2620HPE/C supports priority retagging and complicated flow classification based on VLAN, MAC, source address, destination address, IP or priority, better streamlining services. DG-GS2620HPE/C provides flexible bandwidth control policies, supporting port-/flow-based flow limit, ensuring the line speed forwarding of each port. It supports multiple queue scheduling algorithms such as SP, WRR and "SP + WRR".

Security+

Equipment-level security: The advanced hardware infrastructure design realizes the level-based packet schedule and packet protection, prevents DoS-/TCP- related SYN Flood, UDP Flood, Broadcast Storm or large traffic attacks, and supports level-based command line protection endowing different levels of users with different management permissions.

Perfect security authentication mechanisms: IEEE 802.1x, Radius and TACACS+, storm/multicast/unicast limit and perfect ring detection mechanism, ensuring the long-term stable running of network are supported on the switch. DG-GS2620HPE/C supports port isolation within the same VLAN, DHCP-Snooping, and IP + MAC + Port binding.

Easy Management and Maintenance

DG-GS2620HPE/C supports many management modes such as the CLI, Telnet, SSH, SSL and SNMP; FTP, TFTP, SFTP. DG-GS2620HPE/C supports WEB management mode, which is easy and efficient for installing and debugging the device. ISSU (In-Service Software Upgrade) supports easy software upgrades.

DG-GS2620HPE/C can also be managed through SNMP and NMS, ZTP for smart network management. The combination realizes automatic equipment discovery, network topology management , equipment configuration management , performance data statistics and analysis and trouble management.

DIGISOL®

SWITCHING SOLUTIONS

INDIA'S OWN IT NETWORKING CHOICE

Technical Specifications:-

Item	DG-GS2620HPE/C
Interface	16 GE PoE ports, 2 GE TX/SFP combo ports, 2 100/1000M SFP ports
Console	1 RJ45 port, 1 RST button
Backplane	40 Gbps
Forwarding rate	30 Mpps
Chassis	
Dimensions (WxDxH) (mm)	440x210x44
Weight (KG) (empty)	2.8
Package Dimensions (WxDxH) (mm)	555x295x88
Power consumption	
Weight (KG)	3.9
No-load	< 15W
Full-load	261.4W
Power supply	AC: 100V-240V, 50-60Hz, 265W
PoE power budget	250 W
Total output BTU (1000BTU/H=293W)	892.15
Fan number	2
Noise@25°C (dBA)	37.5
MTBF(H)	>50,000
Forwarding mode	Store-forward
Flash (MB)	16
DRAM (MB)	128
MAC	8K
Buffer size(Mb)	4.1
Jumbo frame	9K
Total SVI	10

MAIN FEATURES:

Item	DG-GS2620HPE/C
VLAN	4K Active VLAN
	QinQ & Selective QinQ
	GVRP, Private VLAN, Voice-VLAN
Spanning Tree	802.1D (STP)
	802.1W (RSTP) and 802.1S (MSTP)
	BPDU guard, root guard and loopback guard
Multicast	IGMP v1/v2/v3, IGMP Snooping, IGMP Fast Leave
	MVR, IGMP filter
IP	Static route, RIP, OSPF,
	128 Routing Table
	IPv4 Dual stack
	DHCP Server/Client/Relay
QoS	CAR, HQoS MAC/IP/TCP/UDP/VLAN/COS/DSCP/TOS based
	QoS 802.1P/ DSCP priority re-labeling, SP, WRR, and SP+WRR
	Tail-Drop, WRED, flow monitoring and traffic shaping

DIGISOL®

SWITCHING SOLUTIONS

INDIA'S OWN IT NETWORKING CHOICE

Technical Specifications:-

MAIN FEATURES:

Item	DG-GS2620HPE/C
Security	Port isolation, Port security and IP+MAC+port binding, MAC sticky DHCP snooping/option82
	DAI & IP source guard, PPPoE+
	IEEE 802.1x, AAA Radius and TACACS+
	L2/L3/L4 ACL flow identification & filtration Anti-attack from DDoS, TCP's SYN Flood, UDP Flood, etc.
	Broadcast/multicast/unknown unicast storm-control
	MD5, SHA-256, RSA-1024, AES256, etc.
Reliability	Static/LACP link aggregation, Interface backup
	EAPS and ERPS
	ISSU
Management	Console, Telnet, SSH v1/2, HTTP, HTTPS, SNMP v1/v2/v3, RMON
	TFTP, FTP, SFTP
	NTP, ZTP (Zero Touch Provisioning)
	SPAN, RSPAN
Accessories	Power cord, Rackmount kits
	Console cable, Anti Slipping Pad
Environment	Operating temperature: -10°C -50°C
	Operating humidity: 10%-90% non-condensing
	Storage temperature: -20°C to -70°C
	Storage humidity: 5%-95% non-condensing

Rear View :



Ordering Information:-

DG-GS2620HPE/C: DIGISOL L3 Lite fully managed Switch with 10/100/1000Mbps PoE/PoE+ ports, 2 Gigabit RJ45/SFP Combo ports and 2 Gigabit fixed SFP ports. Supports Single AC power supply, 110~240V, 50-60Hz.

*Warranty shall be subject to terms and conditions specified in the DIGISOL PRODUCT WARRANTY displayed on the website of the company.

DIGISOL Logos are trademarks and/or registered trademarks of DIGISOL SYSTEMS LIMITED. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here.© 2026 DIGISOL SYSTEMS LIMITED. All rights reserved.

DIGISOL SYSTEMS LIMITED
CITIPOINT, 7th Floor,
Unit No. B-701, B-702 & B-703,
Andheri-Kurla Road, J. B. Nagar,
Andheri (East),
Mumbai - 400059, INDIA

1800-209-3444
www.digisol.com
helpdesk@digisol.com

@DIGISOLINDIA